

DS-3E0106HP-E**4 Port Fast Ethernet Unmanaged POE Switch**

- Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime.
- Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters.
- 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables.
- 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment.
- Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.

▪ Specification

Model		DS-3E0106HP-E
Network Parameters	Ports	4 × 10/100 Mbps PoE port, 2 × 10/100 Mbps RJ45 port
	MAC Address Table	2 K
	Switching Capacity	1.20 Gbps
	Packet Forwarding Rate	0.89 Mpps
	Internal Cache	768 Kbits
PoE Power Supply	PoE Standard	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
	PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
	PoE Port	Hi-PoE: Port 1 PoE: Ports 2 to 4
	Max. Port Power	30 W
	PoE Power Budget	Port 1: 60 W Ports 2 to 4: 30 W
Dialing Function	Long Range	Ports 1 to 4: up to 300 m Long range performance may vary depend on camera model or cable condition.
General	Shell	Metal material, fan-free design
	Net Weight	0.24 kg (0.53 lb)
	Gross Weight	0.77 kg (1.70 lb)
	Dimensions (W × H × D)	145 mm × 25.6 mm × 68.45 mm (5.7" × 1.0" × 2.7")
	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating Humidity	5% to 95% (no condensation)
	Relative Humidity	5% to 95% (no condensation)
	Power Supply	48 VDC, 1.35 A
	Max. Power Consumption	65 W
	Power Consumption in Idle	5 W
	Installation Mode	Desk-Mounted, Wall-Mounted
	Surge Protection	6 KV
Approval	EMC	FCC (47 CFR Part 15, Subpart B), CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020), IC (ICES-003: Issue 7:2020), RCM (AS/NZS CISPR 32: 2015)
	Safety	UL (UL 60950-1), CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
	Chemistry	CE-RoHS (2011/65/EU)

▪ Appearance



▪ Available Model

DS-3E0106HP-E

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

