



RACK

CABLING

WPC-KEY-5U-180/BL

CAT 5E KEYSTONE MODULE 180°, UNSHIELDED, BLACK



Description

- Transmission properties: Category 5e - Area of application: Up to 100 MHz, 10/100Base-T, 1GBase-T - RJ45 female, 8P8C, unshielded - Cable installation via LSA strips, color coded according to EIA/TIA 568 A & B - Dual IDC type, 180 degree - Dust cover for IDC Electrical properties: - Voltage rating: 125 VAC RMS - Current Rating: 1,5 AMP - Contact resistance: < 100 MilliOhm - Insulation resistance: > 1000 MOhm @ 500 VDC - Dielectric strength: 750 VAC RMS 60Hz, 1 min Environmental properties: - Storage: -40o C to +85 oC - Operation temperature: -0o C to +70 oC Mechanical properties: - Housing material: PC - Insert material: Frame Retardancy PBT - PCB material: FR-4 TiÜ1,6mm - Contact material: Phosphor bronze stamp PIN TiÜ0,30mm - IDC Contact material: Phosphor bronze TiÜ0,50mm with tin plating - Mating cycles RJ45: > 750 times - Clamp: > 200 times - IDC wire size: 23 26 AWG



RACK

CABLING

Features

COLOR: black

CATEGORY: 5e

CONNECTOR TYPE A: RJ45

SHIELDING: UTP

PRODUCT: WPC-KEY-5U-180/BL

EAN CODE: 8056045879318