

## ENGLISH

ISIDE is a 105 dB power auto supplied sounder could be configured as positive missing/giving or negative missing/giving. It features a low consumption led flasher and a STAND BY LED. The STAND BY indicator is flashing constant at 1 sec. the LED flasher to indicate that the system is powered and running.

DIP 1		ON = STAND BY MODE ENABLE
DIP 2	DIP 3	
OFF	OFF	Missing positive
ON	OFF	Giving positive
OFF	ON	giving negative
ON	ON	Missing negative

The system also provides the alarm signal, when it is absent one of the power cable.

**TAMPER:** N.C. Antiopening and Tearing Off Contact

**SUPPLY+ - :** 13,8 V Supply ( Nominal )

**S :** Trig Terminal

**Battery:** Battery charge terminal (12V 2.2Ah)

## TECHNICAL SPECIFICATIONS

Nominal Supply Voltage:	13,8 Vcc
Functioning Voltage Limits:	11 , 15 Vcc
Maximum Current Consumption:	150mA
Stand-by Current Consumption:	8 mA
Sound Pressure (Vn=13,8V):	Type = TONE 105 dB(A) at 1 m
Sound and Light Timing without control:	5' ± 20%
Back-up Battery:	12 V , 2,2 Ah
Dimensions:	330mm(L) x 220mm(H) x 60mm(P)
Weight:	700g
Working Temperature:	- 40 °C , + 60 °C

