

Single Door Magnetic Lock for 350kg / 800Lbs

Specification:

Lock Size: 250Lx58Wx29H(mm), double door lock: 500L * 57W * 29H (mm)

Armature plate: 180Lx42Wx13H(mm)

Holding Force: 350kg(800Lbs)

Voltage: 12 / 24VDC

Materials: Fine copper coil + aluminum housing

Current Draw: 12V/540mA 24V/270mA

Available Bracket: JS-35U, JS-35L, JS-35ZL

Suitable for: Wooden door, Glass door, Metal door, Fireproof door

Surface Temp: $\leq +20$

Operating Temp: $-10 \sim +55^{\circ}\text{C}$ ($14 \sim 131^{\circ}\text{F}$)

Suitable Humidity: 0~90%(non-condensing)

Finishes for Shell: Anodized aluminum

Finishes for Magnetic: Zinc

Finishes for Armature: Zinc

Weight: 2.5kg, JS-350D: 5kg

Standard Packing: 10PCS

Standard carton dimension: 350Lx290Wx170H(mm)

Have CE, ROHS, FCC, MA certification

Series for 350kg EM locks

Model	+, - power	Lock sensor	Timer	Dual LED	Lock Dimension	Single or dual door
JS-350	yes	NO	NO	NO	250Lx58Wx29H(mm)	Single door
JS-350S	yes	yes	NO	YES	250Lx58Wx29H(mm)	Single door
JS-350TS	yes	yes	0/3/6/9S	YES	250Lx58Wx29H(mm)	Single door
JS-350D	yes	NO	NO	NO	500Lx58Wx29H(mm)	double door
JS-350DS	yes	yes	NO	YES	500Lx58Wx29H(mm)	double door
JS-350DTS	yes	yes	0/3/6/9S	YES	500Lx58Wx29H(mm)	double door

