







Management devices

TFT-4.3C	    
	<p>Management and control repeater panel, equipped with a multifunctional user interface consisting of: 4.3" TFT capacitive touch screen display, speech synthesis with customisable vocabulary, multifunctional acoustic signal device.</p> <p>The TFT-4.3C panel automatically recognises the device to which it is connected and consequently adapts its functions to the particular operating context.</p> <p>The panel connected to the bus of the TSA1 and TFA1-298 control panels acts as the control panel repeater panel.</p> <p>The panel connected to the TSM1 extinction module bus acts as the management panel, taking complete control of the module functions.</p> <p>The panel displays the commands that manage the operation of the module and, in the event of activation, makes the sequence of the extinguishing cycle visible, dynamically notifying the countdown of the delays that control the different phases.</p> <p>Supported System Commands: Silencing and Control panel Restoring/Associated Module, Silencing and Siren Restoring, Evacuation, Extinguishing Events, Monitored Mode, Exclusion and Inclusion of devices. Built-in flash memory for vocabulary customisation, manageable from a personal computer as an external disk. RS485 bus connection.</p> <p>Surface or flush box 503 mounting. Refined ultra-thin design. Red cover.</p> <p>Certification integrated in TSA1 series control panels and TSM1 extinguishing module.</p> <p>Item no. TF2TFT43C</p>

TFT-4.3C - Technical and functional specifications

General information	Repeater panel	TFT-4.3C
	Communication protocols	FIRE-BUS
	Addressing	Digital
	Connection	Bus RS485
User interface	Display	Color 4.3" TFT
	Resolution	480 x 272 pixel
	Touch screen	Capacitive
	Infographic	Contextual
	Voice synthesis	Monolingual vocabulary
	Speaker	Multifunction
Equipment	Flash memory	32Mbit
Electrical specifications	Power supply	From serial Bus
	Nominal voltage	24V DC
	Operating voltage	18V...30V DC
	Consumption in stand-by	60mA @ 24V DC
	Maximum consumption	80mA @ 24V DC
Physical specifications	Environmental class	3K5 EN 60721-3-3:1995
	Operating temperature	-5°C...+40°C
	Relative humidity (without condensation)	10%...93%
	Protection class	IP4x
	Casing	ABS
	Dimensions (L x H x D)	154 x 104.6 x 23mm
	Weight	230g
Conformity	Repeater panel approved for use with TFA1-298, TSA1 control panels and TSM1 extinguishing module	

COMPATIBILITY TFT-4.3C	TFA1-298	TFA2-596	TFA4-1192	TSA1	TSM1
	✓	-	-	✓	✓